

LED wall luminaire - shielded with forward throw

BEGA

Application

This wall mounted LED luminaire features a forward throw light distribution and is designed for the general illumination of pathways and walkways from various mounting heights. Downlight applications only.

Materials

Luminaire housing constructed of die-cast marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Clear safety glass with optical texture
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations

Protection class IP64

Weight: 3.7 lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	13.9W
System wattage	17 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	1659 lumens (3000K)
Lifetime at Ta = 15° C	>500,000 h (L70)
Lifetime at Ta = 50° C	101,000 h (L70)

LED color temperature

- ☐ 4000K - Product number + **K4**
- ☐ 3500K - Product number + **K35**
- ☐ 3000K - Product number + **K3**
- ☐ 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.


Available colors ☐ Black (BLK) ☐ White (WHT) ☐ RAL:
☐ Bronze (BRZ) ☐ Silver (SLV) ☐ CUS:

Type:

BEGA Product:

Project:

Modified:



LED wall luminaire - shielded with forward throw

	LED	A	B	C
33817	13.9W	5 1/8"	9 1/8"	5 3/8"

